

Kentucky Erosion Prevention and Sediment Control Guide

A guide to preventing erosion and controlling sediment from construction activities in Kentucky

Hazardous Waste Management

Hazardous waste management practices are policies and procedures that address the problem of stormwater polluted with hazardous or chemical pollutants through spills or other forms of contact.

Following are lists describing the targeted materials and recommended procedures.

Targeted Chemical Materials

- Paints
- Solvents
- Stains
- Wood preservatives
- Cutting oils
- Greases
- Roofing tar
- Pesticides, herbicides, and fertilizer
- Fuels and lube oils
- Antifreeze

Storage Procedures

- Wherever possible, minimize the use of hazardous materials.
- Minimize generation of hazardous wastes on the jobsite.
- Segregate potentially hazardous waste from nonhazardous construction site debris.
- Designate a foreman or supervisor to oversee hazardous materials handling procedures.
- Keep chemicals in appropriate containers (closed drums or similar) and under cover.
- Store chemicals away from drainage ditches, swales, and catch basins.
- Use containment berms in fueling and maintenance areas and where the potential for spills is high.

Waste Handling

- Minimize water usage during paint wash-up. Dispose of paint wash water with other liquid wastes, spread on graveled sites prepared for new concrete pouring, or areas being prepared for paving. Do not dispose of wash water in ditches or stormwater inlets.

- Retain and use all products such as paint, thinners, and so on until supplies are depleted. Do not dispose of liquid wastes on pavement or near ditches or stormwater inlets.
- Allow paint rollers, drop cloths, cans, and other wastes to dry thoroughly, then discard in solid waste containers.
- Recycle or dispose of all liquid wastes in accordance with material safety data sheets.
- Ensure that adequate hazardous waste storage volume is available.
- Ensure that hazardous waste collection containers are conveniently located.
- Do not allow potentially hazardous waste materials to accumulate.
- Enforce hazardous waste handling and disposal procedures.
- Clearly mark on all hazardous waste containers which materials are acceptable for the container.

Disposal Procedures

- Ensure that adequate cleanup and containment materials are available on-site.
- Regularly schedule hazardous waste removal to minimize on-site storage.
- Use only licensed hazardous waste haulers.

Education

- Instruct workers on safety procedures for construction site chemical storage.
- Instruct workers in identification of chemical pollutants.
- Ensure that workers are trained in procedures for spill prevention and response.
- Educate workers of potential dangers to humans and the environment from chemical pollutants.
- Educate all workers on chemical storage and disposal procedures.
- Have regular meetings to discuss and reinforce identification, handling, and disposal procedures (incorporate in regular safety seminars).
- Establish a continuing education program to train new employees.

References

[EPA General Construction Site Waste Management](#)

[EPA Spill Prevention and Control Measures](#)